

# QuickSpecs

## HPE MSR20 Series

### Overview

### HPE MSR20 Series

#### Models

HP MSR20-20 Router	JF283A
HP MSR20-21 Router	JD663B
HP MSR20-40 Router	JF228A

#### Key features

- Converged routing, switching, voice, and security
- Embedded encryption, firewall, and security features
- Modular WAN/LAN interface options
- Unified wired and wireless
- Single pane-of-glass management

#### Product overview

The HPE MSR20 router series is a component of the Hewlett Packard Enterprise FlexBranch solution, which is part of the Hewlett Packard Enterprise FlexNetwork architecture. It features a modular design that delivers unmatched flexibility for small branch offices and small to medium-sized businesses while reducing complexity, simplifying management, and increasing control. MSR20 series routers provide a full-featured, resilient routing platform, including IPv6 and MPLS, up to 180 Kpps forwarding capacity, and 100 Mbps encryption. These products offer lasting investment protection, and help reduce capital and operating expenses. MSR20 series routers provide an agile, flexible network infrastructure that offers the ability to quickly adapt to changing business requirements while delivering integrated, concurrent services on a single, easy-to-manage platform.

#### Features and benefits

##### Quality of Service (QoS)

- **Traffic policing:** supports Committed Access Rate (CAR) and line rate
- **Congestion management:** supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance:** Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Other QoS technologies:** support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

##### Management

- **Industry-standard CLI with a hierarchical structure:** reduces training time and expenses, and increases productivity in multivendor installations
- **Management security:** restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide Telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3:** provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration

## Overview

updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)

- **Debug and sampler utility:** supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP):** synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center:** provides a central information center for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- **Management interface control:** provides management access through modem port and terminal interface; provides access through terminal interface, telnet, or SSH
- **Network Quality Analyzer (NQA):** analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

## Connectivity

- **High-density port connectivity:** provides up to 4 interface module slots and up to 18 Fast Ethernet ports
- **Multiple WAN interfaces:** provide a traditional link with E1, T1, ADSL, ADSL2, ADSL2+, G.SHDSL, ATM, Serial, and ISDN/AM backup; provide high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet and LAN 4- and 9-port Fast Ethernet; provide mobility access with 802.11b/g/n Wi-Fi and 3G
- **Packet storm protection:** protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback:** supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **Flexible port selection:** provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDI-X
- **3G access support:** provides 3G wireless access for primary or backup connectivity via a 3G SIC module certified on various cellular networks; optional carrier 3G USB modems available

## Performance

- **Powerful encryption capacity:** includes embedded hardware encryption accelerator to improve encryption performance
- **Flexible chassis selection:** offers a choice of three routers, meeting different requirements on enterprise branches
- **Excellent forwarding performance:** provides forwarding performance up to 180 Kpps; meets current and future bandwidth-intensive application demands of enterprise businesses

## Resiliency and high availability

- **Backup Center:** acts as a part of the management and backup function to provide backup for device interfaces; delivers reliability by switching traffic over to a backup interface when the primary one fails
- **Virtual Router Redundancy Protocol (VRRP):** allows groups of two routers to dynamically back each other up to create highly available routed environments; supports VRRP load balancing

## Layer 2 switching

- **Spanning Tree Protocol (STP)**  
fully supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

## Overview

- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring:** duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **VLANs:** support up to 4,094 ports or IEEE 802.1Q-based VLANs
- **sFlow:** allows traffic sampling

## Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper:** redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

## Layer 3 routing

- **Static IPv4 routing**  
provides simple, manually configured IPv4 routing
- **Routing Information Protocol (RIP)**  
uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **Open Shortest Path First (OSPF)**  
Interior Gateway Protocol (IGP) uses link-state protocol for faster convergence; supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4)**  
Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS)**  
Interior Gateway Protocol (IGP) uses path vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing**  
provides simple, manually configured IPv6 routing
- **Dual IP stack**  
maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng)**  
extends RIPv2 to support IPv6 addressing
- **OSPFv3**  
provides OSPF support for IPv6
- **BGP+**  
extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6**  
extends IS-IS to support IPv6 addressing
- **IPv6 tunneling**  
is an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Multiprotocol Label Switching (MPLS)**

## Overview

uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks

- **Multiprotocol Label Switching (MPLS) Layer 3 VPN**

allows Layer 3 VPNs across a provider network; uses Multiprotocol BGP (MP-BGP) to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility; supports IPv6 MPLS VPN

- **Multiprotocol Label Switching (MPLS) Layer 2 VPN**

establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies

- **Policy routing**

allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

## Security

- **Access control list (ACL):** supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **Terminal Access Controller Access-Control System (TACACS+)**  
is an authentication tool using TCP with encryption of the full authentication request that provides additional security
- **Unicast Reverse Path Forwarding (URPF):** allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks
- **Network login:** authentication of multiple users per port
- **RADIUS:** eases security access administration by using a user/password authentication server
- **Network address translation (NAT):** supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections; supports blacklist in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances
- **Secure Shell (SSHv2):** uses external servers to securely login into a remote device; with authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers
- **IPSec VPN:** supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication
- **DVPN (Dynamic Virtual Private Network):** collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network; compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

## Convergence

- **Internet Group Management Protocol (IGMP):** is used by IP hosts to establish and maintain multicast groups; supports IGMPv1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM):** is used for IPv4 and IPv6 multicast applications; supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP):** is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks and kept

## Overview

separate from unicast traffic

## Integration

- **Embedded NetStream:** local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- **Embedded VPN firewall:** provides enhanced stateful packet inspection and filtering; delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

## Additional information

- **OPEX savings:** are delivered through the use of a common operating system that simplifies and streamlines deployment, management, and training, thereby cutting costs as well as reducing the chance for human errors associated with having to manage multiple operating systems across different platforms and network layers
- **High reliability:** provides a state-of-the-art unified code base
- **Faster time to market:** engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability
- **Green initiative support:** provides support for RoHS and WEEE regulations

## Product architecture

- **Ideal multiservice platform**  
provides WAN router, Ethernet switch, wireless LAN, 3G WAN, firewall, VPN, and SIP/voice gateway all in one box
- **High-density voice interfaces**  
provide flexible analog and digital voice interface options for easy integration within a wide range of deployments
- **USB interface**  
uses USB memory disk to download and upload configuration files; supports an external USB 3G modem for a 3G WAN uplink
- **SIP trunk**  
the SIP trunk link can carry multiple concurrent calls; the carrier authenticates only the link, rather than carrying each SIP call on the link
- **Embedded service modules for security and voice**  
embedded Voice Co-Processing Modules (VCPMs) and Voice Processing Modules (VPMs) accommodate digital signal processor (DSP) modules for voice packet processing; embedded hardware encryption modules, Standard Network Data Encryption (SNDE) cards, and Advanced Network Data Encryption (ANDE) cards do not occupy I/O slots

## Warranty and support

- **1-year warranty:**  
See <http://www.hpe.com/networking/warrantysummary> for warranty and support information included with your product purchase.
- **Software releases:**  
to find software for your product, refer to <http://www.hpe.com/networking/support> ; for details on the software releases available with your product purchase, refer to <http://www.hpe.com/networking/warrantysummary>

## Configuration

### Build To Order:

**BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.**

#### HP MSR20-20 Router

- 2 - SIC module slots
- 1 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot

JF283A

See Configuration

**NOTE:**1, 2, 9

#### Russian Reduced Encryption

JF283A#A59

#### HP MSR20-21 Router

- 8 - RJ45 LAN ports
- 2 - SIC module slots
- 1 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot

JD663B

See Configuration

**NOTE:**1, 2, 9

#### Russian Reduced Encryption

JD663B#A59

#### HP MSR20-40 Router

- 4 - SIC Module slots
- 2 - ESM Slot
- 1 - VCPM slots
- 2 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot

JF228A

See Configuration

**NOTE:**1, 2, 9

#### Russian Reduced Encryption

JF228A#A59

#### Configuration Rules:

Note 1 AC Power Supply included

Note 2 If this product is ordered for delivery to Russia, it must be ordered with the A59 option (also allowed for other countries desiring Low Encryption), then #A59 is the required option in addition to Localization options.

## Configuration

Note 9            Localization required. (See Localization Menu)

## CTO Models

### CTO Solution Sku

HP MSR CTO Router Solution

- SSP trigger sku

JG500A  
See Configuration  
**NOTE:**10

### CTO Base Sku

HP MSR20-20 Router

- 2 - SIC module slots
- 1 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot
- AC Power Supply included

JF283A  
See Configuration  
**NOTE:**1, 2, 11

HP MSR20-21 Router

- 2 - SIC module slots
- 1 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot
- AC Power Supply included

JD663B  
See Configuration  
**NOTE:**1, 2, 11

HP MSR20-40 Router

- 4 - SIC Module slots
- 2 - ESM Slot
- 1 - VCPM slots
- 2 - VPM slot
- 256MB DDR SDRAM included
- 1 - Compact Flash Slot
- AC Power Supply included

JF228A  
See Configuration  
**NOTE:**1, 2, 11

Configuration Rules:

Note 1            If this Switch is selected integrated to the CTO Switch Solution, Then a Minimum of 1 factory integrated accessory must be ordered and integrated to CTO chassis. See Menu below, option must have a #OD1 to be integrated to the CTO Chassis.

## Configuration

- Note 2            Localization required. (See Localization Menu)
- Note 10           This HPN CTO switch cannot be factory racked. (Future Release)
- Note 11           If the Router Chassis is to be Box Level Factory Integrated (CTO), Then the #OD1 is required on the Router Chassis and integrated to the JG500A - HP MSR CTO Enablement. (Min 1/Max 1 Router per SSP)

## Internal Power Supplies

Internal Power Supplies included

## Modules

### SIC Modules

HP MSR 4-port 10/100 SIC Module	JD573B
• None	See Configuration <b>NOTE:1</b>
HP MSR 9-port 10/100 DSIC Module	JD574B
	See Configuration <b>NOTE:2, 3, 15, 16</b>
HP MSR 1-port 10/100 SIC Module	JD545B
• None	See Configuration <b>NOTE:1</b>
HP 1-port 100Mbt SFP SIC Router Module	JF280A
• min=0 \ max=1 SFP Transceivers	See Configuration <b>NOTE:1, 4</b>
HP MSR 1-port 10/100/1000 SIC Module	JD572A
• min=0 \ max=1 SFP Transceivers	See Configuration <b>NOTE:1, 5</b>
HP MSR 2-port FXO SIC Module	JD558A
• None	
HP MSR 1-port FXO SIC Module	JD559A
• None	
HP MSR 2-port FXS SIC Module	JD560A



## Configuration

<ul style="list-style-type: none"><li>None</li></ul>	
HP MSR 1-port FXS SIC Module	JD561A
<ul style="list-style-type: none"><li>None</li></ul>	
HP MSR 1-port E1-Voice SIC Module	JD575A
<ul style="list-style-type: none"><li>min=0 \ max=1 E1 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 6, 11
HP MSR 1-port T1-Voice SIC Module	JD576A
<ul style="list-style-type: none"><li>min=0 \ max=1 E1 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 7
HP 2p ISDN-S/T Voice Interface SIC Mod	JF821A
<ul style="list-style-type: none"><li>None</li></ul>	See Configuration <b>NOTE:</b> 3
HP MSR 2FXS + 1FXO Voice Intfc SIC Mod	JD632A
<ul style="list-style-type: none"><li>None</li></ul>	See Configuration <b>NOTE:</b> 3
HP MSR 1-port Fractional E1 SIC Module	JD634B
<ul style="list-style-type: none"><li>min=0 \ max=1 E1 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 6 11
HP MSR 1-port Fractional SIC Module	JD538A
<ul style="list-style-type: none"><li>min=0 \ max=1 T1 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 7
HP MSR 2-port Fractional E1 SIC Module	JF842A
<ul style="list-style-type: none"><li>min=0 \ max=2 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 12
HP MSR 1-port Enhanced Serial SIC Mod	JD557A
<ul style="list-style-type: none"><li>min=0 \ max=1 Cable</li></ul>	See Configuration <b>NOTE:</b> 3, 8
HP A-MSR 1-port ADSL over POTS SIC Module	JD537A
<ul style="list-style-type: none"><li>None</li></ul>	See Configuration <b>NOTE:</b> 1
HP MSR 1-port ISDN-S/T SIC Module	JD571A
<ul style="list-style-type: none"><li>None</li></ul>	See Configuration <b>NOTE:</b> 3

## Configuration

HP A-MSR 8-port Async Serial SIC Module <ul style="list-style-type: none"><li>• Must select 1 8AS Communication Cable (min=1 \ max=1 cable)</li></ul>	JF281A See Configuration <b>NOTE:</b> 3, 9
HP 802.11b/g/n Wireless AP SIC Module <ul style="list-style-type: none"><li>• None</li></ul>	JF819A See Configuration <b>NOTE:</b> 1
HP MSR 802.11b/g/n Wless AP SIC Mod (NA) <ul style="list-style-type: none"><li>• None</li></ul>	JG211A See Configuration <b>NOTE:</b> 1
HP MSR 1p 8-wire G.SHDSL (RJ45) DSIC Mod <ul style="list-style-type: none"><li>• None</li></ul>	JG191A See Configuration <b>NOTE:</b> 1, 2, 3
HP MSR 1-port ADSL over ISDN SIC Module <ul style="list-style-type: none"><li>• None</li></ul>	JG056B See Configuration <b>NOTE:</b> 1
HP MSR 16-port Async Serial SIC Module <ul style="list-style-type: none"><li>• Must select 4 HP X260 mini D-28/4-RJ45 0.3m Rtr Cables (min=4 \ max=4 cables)</li></ul>	JG186A See Configuration <b>NOTE:</b> 3,10
HP A-MSR 4-port FXS/1-port FXO DSIC Mod <ul style="list-style-type: none"><li>• None</li></ul>	JG189A See Configuration <b>NOTE:</b> 1, 2, 3
HP A-MSR HSPA/WCDMA SIC Module <ul style="list-style-type: none"><li>• None</li></ul>	JG187A See Configuration <b>NOTE:</b> 1
HP MSR 1-port E1/CE1/PRI SIC Module <ul style="list-style-type: none"><li>• None</li></ul>	JF253B
HP MSR 4G LTE SIC Mod for Verizon <ul style="list-style-type: none"><li>• None</li></ul>	JG742A See Configuration <b>NOTE:</b> 1, 13
HP MSR 4G LTE SIC Mod for ATT <ul style="list-style-type: none"><li>• None</li></ul>	JG743A See Configuration <b>NOTE:</b> 1, 13
HP MSR 4G LTE SIC Mod for Global	JF253B

## Configuration

- None

See Configuration

**NOTE:**1, 13

### Configuration Rules:

Note 1	This module max = 2 on JF228A - HP A-MSR20-40 Router	
Note 2	This Module takes up two slots.	
Note 3	This module is only supported on JF228A - HP MSR20-40 Router	
Note 4	The following Transceivers install into this Module: (Use #0D1 if router is CTO) - if applicable	
	HP X110 100M SFP LC LH40 Transceiver	JD090A
	HP X110 100M SFP LC LH80 Transceiver	JD091A
	HP X110 100M SFP LC FX Transceiver	JD102B
	HP X110 100M SFP LC LX Transceiver	JD120B
Note 5	The following Transceivers install into this Module: (Use #0D1 if router is CTO) - if applicable	
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X120 1G SFP LC LH100 Transceiver	JD103A
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
Note 6	The following E1 Cables install into this Module:	
	HP X260 E1 (2) BNC 75 ohm 3m Rtr Cable	JD175A
	HP X260 E1 BNC 20m Router Cable	JD514A
	HP X260 E1/2 BNC 75 ohm 40m Router Cable	JD516A
Note 7	The following T1 Cables install into this Module:	
	T1 Cable RJ45/RJ45-3m	JD518A
Note 8	The following Cables install into this Module:	
	V.24 Serial Port Cable, DTE, 3m	JD519A
	V.24 Serial Port Cable, DCE, 3m	JD521A
	V.35 Serial Port Cable, DTE, 3m	JD523A
	V.35 Serial Port Cable, DCE, 3m	JD525A
	X.21 Serial Port Cable, DTE, 3m	JD527A
	X.21 Serial Port Cable, DCE, 3m	JD529A
	RS449 Serial Port Cable, DTE, 3m	JF825A
	RS449 Serial Port Cable, DCE, 3m	JF826A
	RS530 Serial Port Cable, DTE, 3m	JF827A
	RS530 Serial Port Cable, DCE, 3m	JF828A

## Configuration

Note 9	If this module is selected Then 1 JD642A - HP X260 SIC-8AS RJ45 0.28m Router Cable is required.	
Note 10	If this module is selected Then 4 - JG263A HP X260 mini D-28/4-RJ45 0.3m Rtr Cable are required to be on the same order.	
Note 11	The following E1 Cables install into this Module:	
	HP X260 E1 RJ45 3m Router Cable	JD509A
	HP X260 E1 RJ45 20m Router Cable	JD517A
Note 12	The following 2E1 Cables install into this Module:	
	HP X260 2E1 BNC 3m Router Cable	JD643A
Note 13	The following Antenna Cables install into this Module:	
	HP MSR 3G RF 2.8m Antenna Cable	JG522A
	HP MSR 3G RF 6m Antenna Cable	JG666A
	HP MSR 3G RF 15m Antenna Cable	JG667A
Note 15	If JF228A is selected, Then the maximum for this module = 2	
Note 16	This module is not supported on the JF283A or JD663B.	

### ESM Modules

HP MSR Encryption Accelerator Adv Mod	JD608A
HP MSR Std Encryption Accelerator Mod	JD609A

### Voice Co-Processing Modules

HP MSR Voice Co-processor Module	JD610A
----------------------------------	--------

### Voice Processing Modules

HP MSR 32-channel Voice Processor Module	JD598A See Configuration <b>NOTE:2, 3</b>
HP MSR 24-channel Voice Processor Module	JD599A See Configuration <b>NOTE:2, 3</b>
HP MSR 16-channel Voice Processor Module	JD600A See Configuration <b>NOTE:2, 3</b>

## Configuration

HP MSR 8-channel Voice Processor Module

JD601A  
See Configuration  
**NOTE:** 2, 3

## Transceivers

### SFP Transceivers

HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LH40 Transceiver	JD120B
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP LC LH40 1550nm XCVR	JD062A
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X125 1G SFP LC LH40 1310nm XCVR	JD061A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC LH100 Transceiver	JD103A

## Cables

HP X260 mini D-28/4-RJ45 0.3m Rtr Cable	JG263A
HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A

## Configuration

HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 E1 (2) BNC 75 ohm 3m Rtr Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1/2 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Router Cable	JD518A
HP X260 T1 Voice Router Cable	JD535A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A

### Remarks:

The following cable is used for RJ45 BNC Conversion -  
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable JD511A

The following Connector is used to extend E1/T1 Cables:  
HP X500 T1/E1 Voice RJ45 Interface Connector JD535A

## Router Options

### Antenna Cables

System (std 0 // max 2) User Selection (min 0 // max 2) per SIC Module (JG742A, JG743A, JG744A)

## Configuration

HP MSR 3G RF 2.8m Antenna Cable	JG522A
HP MSR 3G RF 6m Antenna Cable	JG666A
HP MSR 3G RF 15m Antenna Cable	JG667A

### Compact Flash cards

System (std 0 // max 1) User Selection (min 0 // max 1)

HP X600 1G Compact Flash Card	JC684A See Configuration <b>NOTE:1</b>
-------------------------------	--

HP X600 512M Compact Flash Card	JC685A See Configuration <b>NOTE:1</b>
---------------------------------	--

HP X600 256M Compact Flash Card	JC686A See Configuration <b>NOTE:1</b>
---------------------------------	--

Configuration Rules:

Note 1	These CF Cards are supported on the following routers only:	
	HP MSR20-20 Router	JF283A
	HP MSR20-21 Router	JD663B
	HP MSR20-40 Router	JF228A

## Technical Specifications

### HP MSR20-20 Router (JF283A)

<b>Ports</b>	2 SIC slots 2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full										
<b>Physical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Dimensions</b></td> <td>14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;"><b>Weight</b></td> <td>7.5 lb (3.4 kg)</td> </tr> </table>	<b>Dimensions</b>	14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)	<b>Weight</b>	7.5 lb (3.4 kg)						
<b>Dimensions</b>	14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)										
<b>Weight</b>	7.5 lb (3.4 kg)										
<b>Memory and processor</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Processor</b></td> <td>RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM</td> </tr> </table>	<b>Processor</b>	RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM								
<b>Processor</b>	RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM										
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.										
<b>Performance</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Throughput</b></td> <td>180 Kpps (64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>Routing table size</b></td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	<b>Throughput</b>	180 Kpps (64-byte packets)	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)						
<b>Throughput</b>	180 Kpps (64-byte packets)										
<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)										
<b>Environment</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Operating relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	5% to 90%, noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing		
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)										
<b>Operating relative humidity</b>	5% to 90%, noncondensing										
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)										
<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing										
<b>Electrical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Maximum heat dissipation</b></td> <td>184 BTU/hr (194.12 kJ/hr)</td> </tr> <tr> <td style="vertical-align: top;"><b>Voltage</b></td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;"><b>Maximum power rating</b></td> <td>54 W</td> </tr> <tr> <td style="vertical-align: top;"><b>Frequency</b></td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;"><b>Notes</b></td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	<b>Maximum heat dissipation</b>	184 BTU/hr (194.12 kJ/hr)	<b>Voltage</b>	100-240 VAC	<b>Maximum power rating</b>	54 W	<b>Frequency</b>	50/60 Hz	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Maximum heat dissipation</b>	184 BTU/hr (194.12 kJ/hr)										
<b>Voltage</b>	100-240 VAC										
<b>Maximum power rating</b>	54 W										
<b>Frequency</b>	50/60 Hz										
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
<b>Safety</b>	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J										
<b>Emissions</b>	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001										
<b>Telecom</b>	FCC part 68; CS-03										
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB										
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.										
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.										



## Technical Specifications

### HP MSR20-21 Router (JD663B)

<b>Ports</b>	2 SIC slots 2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 8 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height) <b>Weight</b> 7.5 lb (3.4 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> 180 Kpps (64-byte packets) <b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 5% to 90%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 184 BTU/hr (194.12 kJ/hr) <b>Voltage</b> 00-240 VAC <b>Maximum power rating</b> 54 W <b>Frequency</b> 50/60 Hz <b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
<b>Emissions</b>	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

## Technical Specifications

### HP MSR20-40 Router (JF228A)

<b>Ports</b>	4 SIC slots 2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full										
<b>Physical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Dimensions</b></td> <td>14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;"><b>Weight</b></td> <td>11.9 lb (5.4 kg)</td> </tr> </table>	<b>Dimensions</b>	14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)	<b>Weight</b>	11.9 lb (5.4 kg)						
<b>Dimensions</b>	14.17(w) x 11.3(d) x 1.74(h) in (36 x 28.71 x 4.42 cm) (1U height)										
<b>Weight</b>	11.9 lb (5.4 kg)										
<b>Memory and processor</b>	<b>Processor</b> RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM										
<b>Mounting</b>	Mounts in an EIA standard 19-in. rack										
<b>Performance</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Throughput</b></td> <td>180 Kpps (64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>Routing table size</b></td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	<b>Throughput</b>	180 Kpps (64-byte packets)	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)						
<b>Throughput</b>	180 Kpps (64-byte packets)										
<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)										
<b>Environment</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Operating relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	5% to 90%, noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing		
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)										
<b>Operating relative humidity</b>	5% to 90%, noncondensing										
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)										
<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing										
<b>Electrical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Maximum heat dissipation</b></td> <td>341 BTU/hr (359.76 kJ/hr)</td> </tr> <tr> <td style="vertical-align: top;"><b>Voltage</b></td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;"><b>Maximum power rating</b></td> <td>100 W</td> </tr> <tr> <td style="vertical-align: top;"><b>Frequency</b></td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;"><b>Notes</b></td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	<b>Maximum heat dissipation</b>	341 BTU/hr (359.76 kJ/hr)	<b>Voltage</b>	100-240 VAC	<b>Maximum power rating</b>	100 W	<b>Frequency</b>	50/60 Hz	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Maximum heat dissipation</b>	341 BTU/hr (359.76 kJ/hr)										
<b>Voltage</b>	100-240 VAC										
<b>Maximum power rating</b>	100 W										
<b>Frequency</b>	50/60 Hz										
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
<b>Safety</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
<b>Emissions</b>	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001										
<b>Telecom</b>	FCC part 68; CS-03										
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB										
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.										
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.										
<b>Standards and protocols</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>BGP</b></td> <td>RFC 3214 LSP Modification Using CR-LDP</td> </tr> <tr> <td style="vertical-align: top;">(applies to all products in series)</td> <td>RFC 1163 Border Gateway Protocol (BGP)</td> </tr> <tr> <td></td> <td>RFC 1267 Border Gateway Protocol 3 (BGP-3)</td> </tr> <tr> <td></td> <td>RFC 3215 LDP State Machine</td> </tr> <tr> <td></td> <td>RFC 3246 Expedited Forwarding PHB</td> </tr> </table>	<b>BGP</b>	RFC 3214 LSP Modification Using CR-LDP	(applies to all products in series)	RFC 1163 Border Gateway Protocol (BGP)		RFC 1267 Border Gateway Protocol 3 (BGP-3)		RFC 3215 LDP State Machine		RFC 3246 Expedited Forwarding PHB
<b>BGP</b>	RFC 3214 LSP Modification Using CR-LDP										
(applies to all products in series)	RFC 1163 Border Gateway Protocol (BGP)										
	RFC 1267 Border Gateway Protocol 3 (BGP-3)										
	RFC 3215 LDP State Machine										
	RFC 3246 Expedited Forwarding PHB										

## Technical Specifications

RFC 1657 Definitions of Managed Objects for BGPv4  
RFC 1771 BGPv4  
RFC 1772 Application of the BGP  
RFC 1773 Experience with the BGP-4 Protocol  
RFC 1774 BGP-4 Protocol Analysis  
RFC 1965 BGP4 confederations  
RFC 1997 BGP Communities Attribute  
RFC 1998 PPP Gandalf FZA Compression Protocol  
RFC 2385 BGP Session Protection via TCP MD5  
RFC 2439 BGP Route Flap Damping

### Denial of service protection

CPU DoS Protection  
Rate Limiting by ACLs

### Device management

RFC 1305 NTPv3  
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0  
RFC 2271 FrameWork  
RFC 2452 MIB for TCP6  
RFC 2454 MIB for UDP6

### General protocols

IEEE 802.1D MAC Bridges  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs  
IEEE 802.1s Multiple Spanning Trees  
IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
RFC 768 UDP  
RFC 783 TFTP Protocol (revision 2)  
RFC 791 IP  
RFC 792 ICMP  
RFC 793 TCP  
RFC 826 ARP  
RFC 854 TELNET  
RFC 855 Telnet Option Specification  
RFC 856 TELNET  
RFC 858 Telnet Suppress Go Ahead Option  
RFC 894 IP over Ethernet  
RFC 925 Multi-LAN Address Resolution  
RFC 950 Internet Standard Subnetting Procedure  
RFC 959 File Transfer Protocol (FTP)  
RFC 1006 ISO transport services on top of the TCP: Version 3  
RFC 1027 Proxy ARP  
RFC 1034 Domain Concepts and Facilities  
RFC 1035 Domain Implementation and Specification  
RFC 1042 IP Datagrams

RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)  
RFC 3277 IS-IS Transient Blackhole Avoidance  
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile  
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile  
RFC 3392 Support BGP capabilities advertisement  
RFC 3410 Introduction and Applicability Statements for Internet Standard Management Framework  
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)  
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering  
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec  
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers  
RFC 3784 ISIS TE support  
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit  
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management  
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)  
RFC 3847 Restart signaling for IS-IS  
RFC 4301 Security Architecture for the Internet Protocol  
RFC 5101 Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information  
FRF.1.2 PVC User-to-Network Interface (UNI) Implementation Agreement - July 2000  
FRF.11.1 Voice over Frame Relay Implementation Agreement - May 1997 - Annex J added March 1999  
FRF.12 Frame Relay Fragmentation Implementation Agreement - December 1997  
FRF.16.1 Multilink Frame Relay UNI/NNI Implementation Agreement - May 2002  
FRF.2.2 Frame Relay Network-to-Network Interface (NNI) Implementation Agreement - March 2002  
FRF.20 Frame Relay IP Header Compression Implementation Agreement - June 2001  
FRF.3.2 Frame Relay Multiprotocol Encapsulation

## Technical Specifications

RFC 1058 RIPv1	Implementation Agreement - April 2000
RFC 1071 Computing the Internet Checksum	FRF.7 Frame Relay PVC Multicast Service and Protocol Description - October 1994
RFC 1091 Telnet Terminal-Type Option	
RFC 1122 Host Requirements	FRF.9 Data Compression Over Frame Relay Implementation Agreement - January 1996
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	<b>IP multicast</b>
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 1112 IGMP
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2236 IGMPv2
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1293 Inverse Address Resolution Protocol	RFC 2362 PIM Sparse Mode
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 3376 IGMPv3
RFC 1333 PPP Link Quality Monitoring	<b>IPv6</b>
RFC 1334 PPP Authentication Protocols (PAP)	RFC 1981 IPv6 Path MTU Discovery
RFC 1349 Type of Service	RFC 2080 RIPng for IPv6
RFC 1350 TFTP Protocol (revision 2)	RFC 2292 Advanced Sockets API for IPv6
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2461 IPv6 Neighbor Discovery
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2463 ICMPv6
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 2472 IP Version 6 over PPP
RFC 1519 CIDR	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1534 DHCP/BOOTP Interoperation	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1577 Classical IP and ARP over ATM	RFC 2740 OSPFv3 for IPv6
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1624 Incremental Internet Checksum	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1631 NAT	RFC 3513 IPv6 Addressing Architecture
RFC 1638 PPP Bridging Control Protocol (BCP)	RFC 3596 DNS Extension for IPv6
RFC 1661 The Point-to-Point Protocol (PPP)	<b>MIBs</b>
RFC 1662 PPP in HDLC-like Framing	RFC 1213 MIB II
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2	RFC 1229 Interface MIB Extensions
RFC 1701 Generic Routing Encapsulation	RFC 1286 Bridge MIB
RFC 1702 Generic Routing Encapsulation over IPv4 networks	RFC 1493 Bridge MIB
RFC 1721 RIP-2 Analysis	RFC 1573 SNMP MIB II
RFC 1722 RIP-2 Applicability	RFC 1724 RIPv2 MIB
	RFC 1757 Remote Network Monitoring MIB
	RFC 1850 OSPFv2 MIB
	RFC 2011 SNMPv2 MIB for IP
	RFC 2012 SNMPv2 MIB for TCP
	RFC 2013 SNMPv2 MIB for UDP

## Technical Specifications

RFC 1723 RIP v2  
RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1  
RFC 1812 IPv4 Routing  
RFC 1829 The ESP DES-CBC Transform  
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses  
RFC 1878 Variable Length Subnet Table for IPv4  
RFC 1944 Benchmarking Methodology for Network Interconnect Devices  
RFC 1973 PPP in Frame Relay  
RFC 1974 PPP Stac LZS Compression Protocol  
RFC 1990 The PPP Multilink Protocol (MP)  
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)  
RFC 2091 Trigger RIP  
RFC 2131 DHCP  
RFC 2132 DHCP Options and BOOTP Vendor Extensions  
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements  
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification  
RFC 2280 Routing Policy Specification Language (RPSL)  
RFC 2284 EAP over LAN  
RFC 2338 VRRP  
RFC 2364 PPP Over AAL5  
RFC 2374 An Aggregatable Global Unicast Address Format  
RFC 2451 The ESP CBC-Mode Cipher Algorithms  
RFC 2453 RIPv2  
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols  
RFC 2511 Internet X.509 Certificate Request Message Format  
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)  
RFC 2570 Introduction to Version 3 of the Internet-standard Network Management Framework  
RFC 2644 Directed Broadcast Control  
RFC 2661 L2TP  
RFC 2663 NAT Terminology and Considerations  
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5  
RFC 2694 DNS extensions to Network Address Translators (DNS\_ALG)  
RFC 2702 Requirements for Traffic Engineering Over MPLS  
RFC 2747 RSVP Cryptographic Authentication

RFC 2233 Interfaces MIB  
RFC 2454 IPV6-UDP-MIB  
RFC 2465 IPv6 MIB  
RFC 2466 ICMPv6 MIB  
RFC 2618 RADIUS Client MIB  
RFC 2620 RADIUS Accounting MIB  
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB  
RFC 2737 Entity MIB (Version 2)  
RFC 2863 The Interfaces Group MIB  
RFC 2933 IGMP MIB  
RFC 3813 MPLS LSR MIB

### Network management

IEEE 802.1D (STP)  
RFC 1155 Structure of Management Information  
RFC 1157 SNMPv1  
RFC 1905 SNMPv2 Protocol Operations  
RFC 2272 SNMPv3 Management Protocol  
RFC 2273 SNMPv3 Applications  
RFC 2274 USM for SNMPv3  
RFC 2275 VACM for SNMPv3  
RFC 2575 SNMPv3 View-based Access Control Model (VACM)  
RFC 3164 BSD syslog Protocol

### OSPF

RFC 1245 OSPF protocol analysis  
RFC 1246 Experience with OSPF  
RFC 1587 OSPF NSSA  
RFC 1765 OSPF Database Overflow  
RFC 1850 OSPFv2 Management Information Base (MIB), traps  
RFC 2328 OSPFv2  
RFC 2370 OSPF Opaque LSA Option  
RFC 3101 OSPF NSSA

### QoS/CoS

IEEE 802.1P (CoS)  
RFC 2474 DS Field in the IPv4 and IPv6 Headers  
RFC 2475 DiffServ Architecture  
RFC 2597 DiffServ Assured Forwarding (AF)  
RFC 2598 DiffServ Expedited Forwarding (EF)  
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

### Security

IEEE 802.1X Port Based Network Access Control  
RFC 1321 The MD5 Message-Digest Algorithm  
RFC 2082 RIP-2 MD5 Authentication  
RFC 2104 Keyed-Hashing for Message Authentication

## Technical Specifications

RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2138 RADIUS Authentication
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2209 RSVP-Message Processing
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2246 Transport Layer Security (TLS)
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2865 RADIUS Authentication
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2866 RADIUS Accounting
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
RFC 2973 IS-IS Mesh Groups	<b>VPN</b>
RFC 2985 PKCS #9: Selected Object Classes and Attribute Types Version 2.0	RFC 2403 - HMAC-MD5-96
RFC 2993 Architectural Implications of NAT	RFC 2404 - HMAC-SHA1-96
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 2405 - DES-CBC Cipher algorithm
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2547 BGP/MPLS VPNs
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 3032 MPLS Label Stack Encoding	RFC 2842 Capabilities Advertisement with BGP-4
RFC 3036 LDP Specification	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 3046 DHCP Relay Agent Information Option	RFC 2918 Route Refresh Capability for BGP-4
RFC 3063 MPLS Loop Prevention Mechanism	RFC 3107 Carrying Label Information in BGP-4
RFC 3065 Support AS confederation	<b>IPsec</b>
RFC 3137 OSPF Stub Router Advertisement	RFC 1828 IP Authentication using Keyed MD5
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels	RFC 2401 IP Security Architecture
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels	RFC 2402 IP Authentication Header
RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation
	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
	RFC 2411 IP Security Document Roadmap
	RFC 2412 - OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)
	<b>IKEv1</b>
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)
	RFC 3748 - Extensible Authentication Protocol (EAP)

## Accessories

### HPE MSR20 Series accessories

#### Transceivers

HP X110 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
<b>HP X120 1G SFP LC SX Transceiver</b>	JD118B
<b>HP X120 1G SFP LC LX Transceiver</b>	JD119B
<b>HP X124 1G SFP LC LH40 1310nm Transceiver</b>	JD061A
<b>HP X120 1G SFP LC LH40 1550nm Transceiver</b>	JD062A
<b>HP X125 1G SFP LC LH70 Transceiver</b>	JD063B
HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B

#### Cables

HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 E1 BNC 75 ohm 3m Router Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Router Cable	JD518A
HP X260 T1 Voice Router Cable	JD535A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X260 mini D-28 to 4-RJ45 0.3m Router Cable	JG263A

#### Router Modules

HP MSR Encryption Accelerator Advanced Module	JD608A
HP MSR Standard Encryption Accelerator Module	JD609A
HP MSR 4-port 10/100Base-T Switch SIC Module	JD573B
HP MSR 1-port 10/100Base-T SIC Module	JD545B
HP MSR 1-port 100Base-X SIC Module	JF280A
HP MSR 1-port GbE Combo SIC Module	JD572A



## Accessories

HP MSR 2-port FXO SIC Module	JD558A
HP MSR 1-port FXO SIC Module	JD559A
HP MSR 2-port FXS SIC Module	JD560A
HP MSR 1-port FXS SIC Module	JD561A
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 2-port FXS/1-port FXO SIC Module	JD632A
HP MSR 2-port ISDN-S/T Voice SIC Module	JF821A
HP MSR 1-port E1/Fractional E1 (75ohm) SIC Module	JD634B
HP MSR 2-port E1/Fractional E1 (75ohm) SIC Module	JF842A
HP MSR 1-port T1/Fractional T1 SIC Module	JD538A
HP MSR 1-port Enhanced Sync/Async Serial SIC Module	JD557A
HP MSR 1-port ADSL over POTS SIC Module	JD537A
HP MSR 1-port ADSL over ISDN SIC Module	JG056B
HP MSR 1-port 8-wire G.SHDSL (RJ45) DSIC Module	JG191A
HP MSR 1-port ISDN-S/T SIC Module	JD571A
<b>HP MSR 8-port Async Serial SIC Module</b>	JF281A
HP MSR 16-port Async Serial SIC Module	JG186A
HP MSR 802.11b/g/n Wireless Access Point SIC Module	JF819A
HP MSR 802.11b/g/n Wireless Access Point SIC Module (NA)	JG211A
<b>Memory</b>	
<b>HP X600 1G Compact Flash Card</b>	JC684A
<b>HP X600 512M Compact Flash Card</b>	JC685A
<b>HP X600 256M Compact Flash Card</b>	JC686A
<b>HP MSR20-40 Router (JF228A)</b>	
HP MSR 32-Channel Voice Processing Module	JD598A
HP MSR 24-Channel Voice Processing Module	JD599A
HP MSR 16-Channel Voice Processing Module	JD600A
HP MSR 8-Channel Voice Processing Module	JD601A
HP MSR Voice Co-processing Module	JD610A
HP MSR 9-port 10/100Base-T Switch DSIC Module	JD574B



## Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<p><b>HP X120 1G SFP LC SX Transceiver</b> (JD118B)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.</p>	<b>Ports</b>	1 LC 1000BASE-SX port		
	<b>Connectivity</b>	<b>Connector type</b>	LC	
		<b>Wavelength</b>	850 nm	
	<b>Physical characteristics</b>	<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)	
		<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
	<b>Power consumption maximum</b>		1.0 W	
	<b>Cabling</b>	Maximum distance:		
		<ul style="list-style-type: none"> <li>• FDDI Grade distance = 220m</li> <li>• OM1 = 275m</li> <li>• OM2 = 500m</li> <li>• OM3 = Not Specified by standard</li> </ul>		
		Cable length	up to 550m	
<b>Services</b>	Fiber type	Multi Mode		
	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.			

<p><b>HP X120 1G SFP LC LX Transceiver</b> (JD119B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF</p>	<b>Ports</b>	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)		
	<b>Connectivity</b>	<b>Connector type</b>	LC	
		<b>Wavelength</b>	1300 nm	
	<b>Physical characteristics</b>	<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)	
		<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
	<b>Power consumption maximum</b>		1.0 W	
	<b>Cabling</b>	Cable type:		
		Either single mode or multimode;		
		Maximum distance:		
<ul style="list-style-type: none"> <li>• 550m for Multimode</li> <li>• 10km for Singlemode</li> </ul>				

## Accessory Product Details

		Fiber type	Both
	<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
<hr/>			
<b>HP X125 1G SFP LC LH40 Ports 1310nm Transceiver (JD061A)</b>		1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)	
A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	<b>Connectivity</b>	Connector type	LC
		Wavelength	1310 nm
	<b>Physical characteristics</b>	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
		Maximum distance:	
		<ul style="list-style-type: none"> <li>40km distance</li> </ul>	
			Fiber type
	<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
<hr/>			
<b>HP X120 1G SFP LC LH40 Ports 1550nm Transceiver (JD062A)</b>		1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.	<b>Connectivity</b>	Connector type	LC
		Wavelength	1550 nm
	<b>Physical characteristics</b>	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
		Maximum distance:	
		<ul style="list-style-type: none"> <li>40km distance</li> </ul>	
			Fiber type
	<b>Services</b>	Refer to the Hewlett Packard Enterprise website at	

## Accessory Product Details

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP X125 1G SFP LC LH70 Ports

#### Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

#### Connectivity

#### Connector type

LC

#### Physical characteristics

#### Wavelength

1550 nm

#### Dimensions

2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

#### Full configuration weight

0.04 lb. (0.02 kg)

#### Electrical characteristics

#### Power consumption typical

0.8 W

#### Power consumption maximum

1.0 W

#### Cabling

Cable type:  
Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 70km

Fiber type

Single Mode

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP MSR 8-port Async Serial SIC Module (JF281A)

#### Connectivity

#### Bit rate

115.2Kbps

#### Interface

RS232

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP X600 1G Compact Flash Card (JC684A)

#### Physical characteristics

#### Dimensions

4.96(d) x 8.82(w) x 2.56(h) in. (12.6 x 22.4 x 6.5 cm)

#### Weight

0.33 lb. (0.15 kg)

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP X600 512M Compact

#### Physical characteristics

#### Dimensions

4.96(d) x 8.82(w) x 2.56(h) in. (12.6 x 22.4 x 6.5 cm)

---

## Accessory Product Details

### Flash Card (JC685A)

#### Services

#### Weight

0.33 lb. (0.15 kg)

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HP X600 256M Compact Physical characteristics

### Flash Card (JC686A)

#### Services

#### Dimensions

4.96(d) x 8.82(w) x 2.56(h) in. (12.6 x 22.4 x 6.5 cm)

#### Weight

0.33 lb. (0.15 kg)

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

## Summary of Changes

Date	Version History	Action	Description of Change:
01-Dec-2015	From Version 18 to 19	Changed	Overview and Technical Specifications updated
July 3, 2014	From Version 17 to 18	Changed	Configuration menu updated.
June 17, 2014	From Version 15 to 17	Changed	Updated General Protocols, as well as the AC Voltage specifications.
June 10, 2014	From Version 14 to 15	Changed	The Configuration section was updated.
January 31, 2014	From Version 13 to 14	Changed	Build To Order was revised in Configuration.
November 22, 2013	From Version 11 to 13	Changed	SIC Modules and Cables were revised in Configuration.
September 30, 2013	From Version 10 to 11	Removed	HP X260 T1VI DB15M RJ45 3m Router Cable, HP 1-port Analog Modem SIC MSR Module, and HP 3G Wireless GSM/WCDMA WAN SIC Module were removed from Accessories
September 27, 2013	From Version 9 to 10	Changed	Configuration was revised.
August 9, 2013	From Version 8 to 9	Changed	Notes were revised in CTO Models.
July 12, 2013	From Version 7 to 8	Added	Configuration was added.
April 17, 2013	From Version 6 to 7	Removed	Overview: Features and benefits: Removed 30 calendar day from Warranty and Support.
February 11, 2013	From Version 5 to 6	Changed	Updated the Features and Benefits section and the specifications for each model (weight, dimensions, and Routing table size). Standards and protocols was also updated.
March 26, 2012	From Version 4 to 5	Changed	Features and benefits and Accessories were revised.
November 14, 2011	From Version 3 to 4	Changed	The product name and accessories sections were updated.
October 13, 2011	From Version 3 to 4	Added	Accessory Product Details was added.
March 16, 2011	From Version 2 to 3	Changed	Specifications were revised.
December 30, 2010	From Version 1 to 2	Changed	Minor edits were made within the Accessories section and EMEA was added.

## Summary of Changes



**Sign up for updates**

★ Rate this document



**Hewlett Packard  
Enterprise**

---

© Copyright 2015 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: [www.hp.com/networking](http://www.hp.com/networking)

c04111581 - 13813 - Worldwide - V19 - 1-December-2015